



# BOYSEN® KNOxOUT™ B-8701 Acrylic Air Cleaning Paint

## DESCRIPTION

**BOYSEN® KNOxOUT™** is the first air cleaning paint in the world with **CristalACTiV™** photocatalytic technology. It uses light energy to break down noxious air pollutants and converts them into harmless substances. Any surface coated with KNOxOUT becomes an active air-purifying surface that helps protect people from harmful gases. Photocatalysis also provides KNOxOUT with self-cleaning, antibacterial, and de-odorizing properties.

## SUGGESTED COLORS

B-8701	Purifying White
B-8701N62	Cleansing Ivory
B-8701N52	Aura Green
B-8701N40	Clear Sky Blue
B-8701N71	Refreshing Red
B-8701N33	A Breeze of Gray

## PRINCIPAL USES

BOYSEN KNOxOUT is ideal for areas with high NOx levels. B-8701 Acrylic is best used for interiors such as indoor car parks.

## TECHNICAL DATA

### Vehicle Type:

Acrylic

### Finish:

Flat

### VOC:

2.4 g/L

### Dry Time:

Touch: 1 hour

Recoat: 2 hours

\*Measured at 25°C and 50% relative humidity

\*Local climate conditions may affect the required drying time and recoating interval specified above. For best results, follow the normal painting procedures of your standard latex emulsion paint.

### Density:

1.47 kg/L

### Theoretical Coverage per gallon at 1.8-1.6 mils DFT:

30-35 sq. m.

\*Depending on surface texture and porosity

### Tinting:

All colors should be factory-mixed.

### Thinning Solvent:

Use as supplied. If necessary, thin with not more than ½ Liter of clean water per 1-gallon can.

### Clean-up Solvent:

Water

### Packaging:

1 gallon

### Application:

By brush, roller, or airless spray

## SURFACE PREPARATION

### New Concrete

Allow new concrete to dry for 14-28 days under normal weather conditions before painting. Surface to be painted should be clean and dry, free from oil, grease, dust, dirt, contaminants, and all loose grit and mortar.

### Repainting

Scrape off all loose, scaling, flaking, and peeling paint manually or by using BOYSEN Paint and Varnish Remover B-141, as necessary. Wash surfaces clean and completely remove chemical residue. Let it dry.

For repainting concrete, use BOYSEN Chalk Blocker B-7304 as surface conditioner. In case of mildew infestation, treat with a bleach solution (1:3, laundry bleach to water, respectively) by swabbing or brushing. To ensure proper treatment, let stand for 24 hours before washing off residue. Let dry.

## PAINTING SCHEDULE

1st coat: BOYSEN® EcoPrimer™

Putty: BOYSEN® Masonry Putty B-7311 (for interior use)

2nd & 3rd coat: BOYSEN® KNOxOUT™ Air Cleaning Paint B-8701 Acrylic (for interior use)

## SHIPPING

**UN Number:** Not Applicable

**Freight Classification:** Non-DG

**Flash Point:** Not Applicable

## PRECAUTIONS

**Health & Safety:** Ensure good ventilation during application and drying. Avoid breathing vapor and spray mist. Avoid contact with skin and eyes. Wear eye protection and gloves during application or sanding. Wash hands thoroughly after.

This product is not recommended for toys and other children's products. Do not take internally. Keep out of reach of children.

In case of spillage, keep spectators away. Dike and contain spills with inert material (e.g. sand or earth). Keep spills and cleaning runoffs out of sewers and open bodies of water. Dispose contaminated material according to government regulations.

**First aid:** If overcome by vapor and spray mist, bring victim to fresh air. If discomfort persists or any breathing difficulty occurs, get medical help. In case of eye contact, rinse immediately with plenty of water for at least 15 minutes and obtain medical help at once. In case of skin contact, wash thoroughly with soap and water. Remove contaminated clothing. Wash clothes before reuse. If swallowed, do not induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into the lungs. Get medical help at once.

## LIMITATIONS ON LIABILITY

To the best of our knowledge the technical data contained herein are true and accurate at the date of issuance but are subject to change without prior notice. We guarantee our product to conform to Pacific Paint (BOYSEN) Philippines, Inc.'s specifications. We make no other warranty or guarantee of any kind, express or implied, including merchant ability and fitness for particular purpose. Labor or cost of labor and other consequential damages are hereby excluded.



### PACIFIC PAINT (BOYSEN) PHILIPPINES, INC.

#### MAIN OFFICE:

292 D. Tuazon Street, Quezon City, Philippines 1115

Tel. Nos. (02) 364-3505 to 09; (02) 365-0561 to 64

Fax Nos. (632) 361-7164; 367-8881

[inquiry@boysen.com.ph](mailto:inquiry@boysen.com.ph)

[www.boysen.com.ph](http://www.boysen.com.ph)

#### MARKETING AND TECHNICAL OFFICE:

269 D. Tuazon Street, Quezon City, Philippines 1115

Tel. Nos. (632) 366-3962; 363-9738; 330-9662; 367-8880

Fax Nos. (632) 367-8878

[marketing@boysen.com.ph](mailto:marketing@boysen.com.ph)

[technical@boysen.com.ph](mailto:technical@boysen.com.ph)